

# Optimax

The Industry's Most Popular Lightbar

|                |                    |
|----------------|--------------------|
| <b>Height:</b> | 130mm (5")         |
| <b>Width:</b>  | 290mm (11.4")      |
| <b>Length:</b> | Up to 1741mm (68") |



- Exceptional light output with a combination of 360° and standard LED options
- Gear driven halogen rotators for long life
- Easy maintenance, quick release one piece lenses
- UV stabilised polycarbonate lens
- Reg 65 Class 1 Blue and Amber option
- Chapter 8 Amber option

Optional bespoke lettering and logo's available for all Premier Hazard lightbar illuminated centre sections.



**CONTACT OUR SALES TEAM TO DISCUSS YOUR BESPOKE SPECIFICATION.**



**Other lengths**

|              |
|--------------|
| 510mm (20")  |
| 694mm (27")  |
| 849mm (33")  |
| 1036mm (41") |
| 1114mm (44") |
| 1214mm (48") |
| 1374mm (54") |
| 1476mm (58") |
| 1741mm (68") |

**Lens Colours**



**Options**

- LED's
- Rotator Assemblies
- Halogen Warning
- Strobe Heads
- Strobe Power Supplies
- Signs & Grilles
- Spot/Flood Lighting
- Infosigns
- Speakers
- Roof Connector

